

Revised on January 2013

HAWK-SEAL



FEATURES:

- Composed of no asphalt, Hawk-Seal provides a special High-Tack feature only found in butyl.
- Use Hawk-Seal on joints in: Box culverts, manholes, concrete pipe, septic tanks, utility boxes and vaults.
- No special tools needed
- Designed for flexibility in temperature extremes
- Excellent chemical resistance
- Hawk-Seal tolerates joint deflection
- Plastic film backing for easy tear resistant release

DIRECTIONS:

- Joint surface should be clean and dry. Unroll the sealant onto the joint. Light pressure on the release film side of the sealant will help to keep the sealant in place. After the entire joint has sealant in place leave the release paper intact until the joint is about to be sealed.
- When joining two ends of Hawk-Seal avoid overlapping sealant. Use the splicing method.
- Splicing Method: Butt the two ends together without overlapping. The two ends then will fuse together after light pressure.

Note: To find annular space to be filled subtract the outside diameter of the tongue from the inside diameter of the groove and divide by two.

ITEM NUMBER – SIZE	ROLL LENGTH	ROLLS/CARTON	CARTONS/PALLET
5820-HKS-001.....1/2"	26"	12	27
5821-HKS-001.....3/4"	14' 6"	10	36
5823-HKS-001.....1"	14'6"	8	36
5824-HKS-001....1 1/4"	14' 6"	6	36
5825-HKS-001....1 1/2"	10'	6	36
5827-HKS-001.....2"	7'	4	36

Meets ASTM C-990-01A and AASHTO M-198 and SS-S-210

Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and material safety data sheets before using. While all statements, technical information, and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user.

Please contact ErgonArmor for further information at 877.982.7667 or FAX 601-933-3381. For all Terms and Conditions of Sale see ergonarmor.com.

ORDERING INFORMATION

For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call 877-98ARMOR.



ErgonArmor
TECHNICAL COATING SOLUTIONS®

A Division of Ergon Asphalt & Emulsions, Inc. | P.O. Box 1639, Jackson, MS 39215-1639
| 601-933-3381 Fax | 877-98ARMOR | ergonarmor.com