

Revised on January 2013

BH5011 LIQUID ASPHALT COATING



DESCRIPTION:

Blackhawk Liquid Asphalt Coating is a liquefied asphalt damp proofing compound formulated to be easily applied by roller brush or spray equipment. Blackhawk Liquid Asphalt Coating can be used as a primer on surfaces to receive Blackhawk Pipe Joint Mastic, Hawk-Seal, and Hawk-Wrap, or as a coating. It dries to a tough, durable, and water-deterring layer that maintains excellent performance over a wide range of temperatures and conditions.

SURFACE PREPARATION:

Surface must be clean, dry and free from oil, grease, dirt, dust, and all other loose impediments to ensure excellent adhesion.

APPLICATION:

Apply to surface by brush, spray, or roller application. Material is ready to use as supplied. Do not thin with additional solvents.

BRUSH APPLICATION:

Apply with a wide fiber brush in order to create a smooth uniform film.

ROLLER APPLICATION:

Use appropriate roller size to cover the particular surface to be coated. Dip the entire head of roller into coating and allow dripping for a few seconds before use.

SPRAY APPLICATION:

Utilize a standard heavy-duty airless spray pump. Consult spray equipment manufacturers for details regarding pump ratio, spray tip, and hose requirements. Allow film to cure for at least 24 to 48 hours.

COVERAGE RATE:

Recommended coverage rate is approximately 1-gallon per 300 square feet. Application rates may vary depending upon the surface absorption rate.

PACKAGING:

Available in 5-gallon pails, 55-gallon drums, and 275-gallon plastic totes.

CARE OF TOOLS:

Dried material on equipment and brushes may be cleaned and removed with mineral spirits.

Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and material safety data sheets before using. While all statements, technical information, and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user.

Please contact ErgonArmor for further information at 877.982.7667 or FAX 601-933-3381. For all Terms and Conditions of Sale see ergonarmor.com.

ORDERING INFORMATION

For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call 877-98ARMOR.



ErgonArmor
TECHNICAL COATING SOLUTIONS®

A Division of Ergon Asphalt & Emulsions, Inc. | P.O. Box 1639, Jackson, MS 39215-1639
| 601-933-3381 Fax | 877-98ARMOR | ergonarmor.com