



## PRODUCT INFORMATION

---

*Revised on January 2013*

### **BH5109 ASPHALT CUTBACK**

***DESCRIPTION:***

An asphalt-solvent blend containing high quality asphalt and a petroleum solvent. It contains no fillers or fibers. It may be used as an asphalt pavement sealer or primer.

***TYPICAL PROPERTIES PROPERTIES :***

Viscosity, Brookfield @ 77F.....	< 1500 cps
Solids Content Wt. %.....	59 +/- 1
Specific Gravity.....	0.9112
Density, Pounds Per Gallon.....	7.60
Flash Point, T.O.C., F., Min.....	100
Base Asphalt Characteristics	
Softening Point, °F., R&B.....	175-180
Penetration at 77°F.....	5-15

Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and material safety data sheets before using. While all statements, technical information, and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user.

Please contact ErgonArmor for further information at 877.982.7667 or FAX 601-933-3381. For all Terms and Conditions of Sale see [ergonarmor.com](http://ergonarmor.com).

***ORDERING INFORMATION***

For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call 877-98ARMOR.



A Division of Ergon Asphalt & Emulsions, Inc. | P.O. Box 1639, Jackson, MS 39215-1639  
| 601-933-3381 Fax | 877-98ARMOR | [ergonarmor.com](http://ergonarmor.com)