



**Blackhawk®**

A Division of ErgonArmor

## PRODUCT INFORMATION

---

*Revised on January 2013*

### **BH5400 ROOF FLASHING CEMENT**

**DESCRIPTION:**

BH5400 is asbestos free, fiber-reinforced asphalt roofing cement. Composed of select asphalt and special grade solvent, this material has a smooth troweling consistency.

**USAGE:**

BH5400 has a variety of uses including: night seals, vertical flashings, three coursing, setting roof drains, adhering membrane material in repair situations, end lap sealing and a variety of other roof top applications.

**SURFACE PREPARATION:**

For best adhesion be sure all substrates are free from ponded water, clean and free from oil, grease, rust scale, loose paint, dirt dust or debris that would interfere with surface contact to substrate.

**APPLICATION:**

Irregular, dirty or porous surfaces should be primed before application of BH5400.

Material is trowel applied to a thickness not to exceed 1/4". Coverage rates are 14 square feet per gallon at 1/8" thickness.

**PACKAGING:**

BH5400 is available in 5-gallon pails (net contents 4.7-gallons).

**PHYSICAL PROPERTIES**

Appearance.....	Smooth, black mastic material
Viscosity.....	Trowel Grade
% Solids by weight.....	Minimum 83%
Flash Point.....	>105°F
VOC Content.....	<250 g/l
Weight per gallon.....	9-10

Meets ASTM D-4586 Type I

Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and material safety data sheets before using. While all statements, technical information, and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user.

Please contact ErgonArmor for further information at 877.982.7667 or FAX 601-933-3381. For all Terms and Conditions of Sale see [ergonarmor.com](http://ergonarmor.com).

### **ORDERING INFORMATION**

For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call 877-98ARMOR.



**ErgonArmor**  
TECHNICAL COATING SOLUTIONS®

A Division of Ergon Asphalt & Emulsions, Inc. | P.O. Box 1639, Jackson, MS 39215-1639  
| 601-933-3381 Fax | 877-98ARMOR | [ergonarmor.com](http://ergonarmor.com)