

Revised on January 2013

BH 5401 PIPE JOINT MASTIC



DESCRIPTION:

Blackhawk Pipe Joint Mastic is a tough, permanent bituminous sealer of heavy trowel consistency that is impervious to water, sewage, and roots. This material seals precast concrete storm and sanitary joints and will not crack or deteriorate under normal service conditions.

USES:

Blackhawk Pipe Joint Mastic is used to seal and connect intersections of pipe and culverts and create a watertight seal in sewer systems.

SURFACE PREPARATION:

Clean surface where mastic is to be applied using a brush to rid surface of all loose impediments. If necessary, prime area where Blackhawk Pipe joint Mastic will be applied with Blackhawk Liquid Asphalt Coating. This will maximize adhesion and sealing.

TROWEL APPLICATION:

Apply to surface with trowel or gloved hand. Form a layer of mastic so that it creates a 45° slope off of the top of the pipe joint and thinning out towards the end of the pipe.

PACKAGING:

Blackhawk Pipe Joint Mastic is available in 5-gallon pails.

CARE OF TOOLS:

Dried material on equipment may be cleaned with mineral spirits.

CAUTION:

For industrial use only. Keep out of reach of children. Dispose of empty containers in accordance with all local, state, and federal regulations. Read Material Safety Data Sheet (MSDS) before using this product.

SPECIFICATIONS

D4586 Type I

Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and material safety data sheets before using. While all statements, technical information, and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user.

Please contact ErgonArmor for further information at 877.982.7667 or FAX 601-933-3381. For all Terms and Conditions of Sale see ergonarmor.com.

ORDERING INFORMATION

For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call 877-98ARMOR.



ErgonArmor
TECHNICAL COATING SOLUTIONS®

A Division of Ergon Asphalt & Emulsions, Inc. | P.O. Box 1639, Jackson, MS 39215-1639
| 601-933-3381 Fax | 877-98ARMOR | ergonarmor.com