



PRODUCT INFORMATION

Revised on January 2013

BH5600 PREMIUM ROOF CEMENT

DESCRIPTION:

BH5600 is an asbestos free, fiber-reinforced, premium asphalt roof cement suitable for trowel application to roofing and flashing. BH5600 has excellent vertical slump resistance. This product exhibits a smooth consistency easily applied by the roofing professional.

USAGE:

Primary use is in construction of roof flashings and other commercial roofing details. It can be used in both vertical and horizontal situations.

SURFACE PREPARATION:

For best adhesion be sure all substrates are free from ponded water, clean and free from oil, grease, rust scale, loose paint, dirt, dust and debris that would interfere with surface contact and act as a bond breaker.

APPLICATION:

Irregular, dirty, or porous surfaces should be primed before application of BH5600. Material is trowel applied to a thickness not to exceed 1/4". This material will resist slump when reinforced with glass fabric in 3-coursing situations. Coverage rates are 14 square feet per gallon at 1/8" thickness.

PACKAGING:

BH5600 is available in 5-gallon pails (net contents 4.7-gallons).

PHYSICAL PROPERTIES

Meets ASTM D4586 Type I

Appearance	Black Mastic
Viscosity	Trowel Grade
% Solids by weight	Minimum 70%
Flash Point	>105°F
VOC content: g/l	<350
Weight per Gallon	8.4-8.9
Cone Penetration 77°F, 150 gr, and 5-seconds	250-300

Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and material safety data sheets before using. While all statements, technical information, and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user.

Please contact ErgonArmor for further information at 877.982.7667 or FAX 601-933-3381. For all Terms and Conditions of Sale see ergonarmor.com.

ORDERING INFORMATION

For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call 877-98ARMOR.



ErgonArmor
TECHNICAL COATING SOLUTIONS®

A Division of Ergon Asphalt & Emulsions, Inc. | P.O. Box 1639, Jackson, MS 39215-1639
| 601-933-3381 Fax | 877-98ARMOR | ergonarmor.com