



**Blackhawk®**  
A Division of ErgonArmor

**BH 5700**

## **PRODUCT INFORMATION**

---

*Revised on January 2013*

### **BH5700 COMMERCIAL ROOFING ADHESIVE/SEALANT**

#### **PRODUCT DESCRIPTION:**

BH5700 Multi-Purpose Adhesive/Sealant is a two-component, cold-applied polymeric compound. After the components are mixed, a chemical reaction in situ forms an elastomeric polymer with numerous excellent properties. BH5700 contains low levels of VOC's complying with nearly all VOC's restrictions. Product is combustible not flammable.

#### **PRODUCT USES:**

BH5700 can be used in the following application:

- Membrane/interply adhesive in full coverage
- Insulation adhesive in full coverage or ribbon spacing
- Monolithic membrane system reinforced or un-reinforced
- Liquid applied membrane for penetration details
- Pitch pan sealer

#### **COVERAGE:**

Typical application rates in full coverage are 1.5-2 gallons per square. Irregular or porous substrates may require 2.5 gallons per square or more. ¼" serrated squeegees are used to apply material.

#### **MIXING:**

Utilize a heavy duty ½" drill capable of 450 to 900 rpm. Mixing blade should be a 5" diameter barrel prop mixer. Premix for 1 minute to reduce viscosity. Then add component 2 to component 1 and mix thoroughly for 3 minutes.

#### **PRODUCT INFORMATION:**

Unit: 5-gallon pails Pallet Size: 48" x 45"

Net Contents: 4-gallons Weight per pail: 36.5

Packaging: 14 per layer on 3 layers Weight per pallet: 1533

Pails per pallet: 42 Pallets per truck load: 24

#### **HARDENER PACKAGING:**

Hardeners are packed under the lid of the base material seated on a plastic shelf. This packaging allows for kit packaging which creates a quality assurance mechanism that ensures mixing personnel are alerted the fact that this is 2-part product. Mix instructions are also packaged under the lid on shelf with every kit.

Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and material safety data sheets before using. While all statements, technical information, and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user.

Please contact ErgonArmor for further information at 877.982.7667 or FAX 601-933-3381. For all Terms and Conditions of Sale see [ergonarmor.com](http://ergonarmor.com).

### **ORDERING INFORMATION**

**For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call 877-98ARMOR.**



**ErgonArmor**  
TECHNICAL COATING SOLUTIONS®

A Division of Ergon Asphalt & Emulsions, Inc. | P.O. Box 1639, Jackson, MS 39215-1639  
| 601-933-3381 Fax | 877-98ARMOR | [ergonarmor.com](http://ergonarmor.com)