



PRODUCT INFORMATION

Revised on January 2013

BH5800 VERSATAK

DESCRIPTION:

VersaTak is an extruded polymer modified asphalt product provided in the lengths, thickness and widths that fit the application. As a preformed adhesive/sealant, the applicator will never over-apply or under-apply quantity needed thus reducing waste or preventing failure due to lack of adhesive.

VersaTak is extruded on a treated paper to give an easy release application. The product comes in roll form up to 200' in length and 12" in width. VersaTak can also be laminated to a HDPE sheet to give extreme puncture and tear resistance.

Additionally, this product can be made into circular DOTS up to 12" diameter and 1/2" thickness. If no shape or tape form is required, then the product can be supplied as a hot melt material (2.5# bricks, 5-gallon pails or 55-gallon release treated fiber drums or steel drums) with hundreds of potential applications.

USES:

This unique tape product exhibits a wide range of functional uses due to its aggressive tack, elasticity, elongation, and waterproofing characteristics. Whether used in tape, DOT, or hot applied fashion, VersaTak forms tenacious bonds with concrete, asphalt, plywood, metal, expanded polystyrene insulation, extruded polystyrene insulation, and many plastics. Basically, any two or more products that need to be bonded or layered together may utilize this tape product to do so.

BENEFITS:

Since the product is a solid, it is simply "peel-n-stick". No cure or dry time is needed as compared to solvent-based adhesives that will dissolve or damage the materials being joined. There is no wasted product like you may see with liquid adhesive residue and little trash. The release paper and box can be recycled.

In colder to freezing climates, the product can be heat activated. This will provide extreme tack in the coldest climates and will not degrade the polymer if only heated for a 5 second or less time period.

TECHNICAL:

Thickness on tape products.....up to 100 mils
Softening Point.....215°F min
Color.....Black

Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and material safety data sheets before using. While all statements, technical information, and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user.

Please contact ErgonArmor for further information at 877.982.7667 or FAX 601-933-3381. For all Terms and Conditions of Sale see ergonarmor.com.

ORDERING INFORMATION



ErgonArmor
TECHNICAL COATING SOLUTIONS®

A Division of Ergon Asphalt & Emulsions, Inc. | P.O. Box 1639, Jackson, MS 39215-1639
| 601-933-3381 Fax | 877-98ARMOR | ergonarmor.com

For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call 877-98ARMOR.