

USAGE PROCEDURE FOR EPEX CLEAN HAZE CLEANER

Short Form Directions For Use

NOTE: Read and familiarize yourself thoroughly with Material Safety Data Sheets before using.

1.0 USE INSTRUCTIONS

- 1.1 The purpose of Epex Clean Haze Cleaner is to remove cured epoxy film from the surface of brick and tile linings. It is not designed to remove thick films or blobs of cured epoxy. Thick films and blobs should first be removed by heating with a hot air gun to soften and loosen them then remove by mechanical means.
- 1.2 Apply a uniform layer of Epex Clean Haze Cleaner to the affected area using a brush or roller. Do not dilute the cleaner or pre-wet the tiles with water. Ensure that the entire area is thoroughly covered with the cleaner. For best results, clean the floor in sections no greater than 300 sq ft (30 sm) at a time.
 - 1.2.1 Packaging of Epex Clean Haze Cleaner is as follows:
Code 28195 - 5 liter (1.3 US gallon) bottle
Code 29511 - 25 liter (6.5 US gallon) pail
 - 1.2.2 Coverage and usage rate of Epex Clean Haze Cleaner is estimated at between 500 and 700 sf per gallon (12-17 sm per l). Coverage can vary depending on variables noted in section 1.9 below, and are not guaranteed.
- 1.3 Allow the cleaner to sit for about 30 minutes to loosen or dissolve residue.
- 1.4 Prevent the cleaner from drying out during contact period. If drying occurs, apply additional cleaner.
- 1.5 Do not use water to re-wet dried areas.
- 1.6 At the end of the contact period, scrub the area vigorously using a stiff brush, scrub pad, or floor scrubber.
- 1.7 Wash away loosened or dissolved residue with soap and water.

- 1.8 Rinse area with clean water and allow area to dry.
- 1.9 A shorter contact time may be adequate for areas with a light haze or areas where a grout residue has not achieved a full and complete cure. A longer time may be needed for heavier residues. Evaluate on a case by case basis using trial and error and depending upon specific site conditions and variables such as age of the haze, tile surface texture, ambient temperatures, etc.
- 1.10 The effectiveness of Epex Clean Haze Cleaner has not been determined on all possible types of residues stains or tile surfaces. This cleaner should be tested on a small, representative area, in the manner described above. The degree of cleanliness in the treated area should be evaluated and approved by the appropriate site personnel prior to cleaning the entire floor.

2.0 SAFETY PRECAUTIONS / DISCLAIMER

- 2.1 Read and follow the safety information provided on the material safety data sheet. USE THIS REFERENCE AS A GUIDE ONLY. THE INFORMATION IS BELIEVED TO BE RELIABLE, BUT NO GUARANTEE IS MADE NOR DO WE ASSUME LIABILITY IN CONNECTION WITH ITS USE. PLEASE CONTACT CORROSION ENGINEERING DEPARTMENT FOR SPECIFIC RECOMMENDATIONS AT (610) 833-4000-1500 OR FAX (610) 833-3040.
- 2.2 Read and follow the hazard information, precautions and first aid directions on the individual product labels and material safety data sheets before using. While all statements, technical information, and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed.
- 2.3 We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user.
- 2.4 Please contact Corrosion Engineering for specific recommendations or questions at +1-610-833-4000 or fax +1-610-833-3040.