



## PRODUCT INFORMATION

---

*Revised on April 2012*

### NOVOTAC

#### **DESCRIPTION:**

NovoTac is a polymer emulsion based primer for self-adhesive membranes. It can be applied to masonry, gypsum board, concrete, wood, and a variety of other surfaces. NovoTac is the product of choice when it is necessary to achieve fast drying, solvent free, tacky surfaces.

#### **FEATURES:**

Quick Drying  
Tacky film provides positive adhesion of membrane  
Easily applied by brush, spray or roller  
Environmentally Friendly – 0 VOC's  
Non Flammable during application  
Water based, no solvent odor

#### **PHYSICAL PROPERTIES**

Color	Custom colors available
Container Size	5 gallons
Drying Time 68 °F	Initial set 30 minutes, full set 2 hours
Flammability	Wet nonflammable, dry burns
Flash Point	greater than 212 °F
Max VOC'S	0g/L
Application temperature	45°-104°F
Theoretical coverage	250-500 Sq. Ft./ Gallon
Viscosity	Water Like
Weight Per Gallon	8.2-8.7 Lbs.
Weight % Solids	50.0%

#### **COVERAGE:**

Up to 500 sq. ft. /gallon depending on porosity and texture of the surface.

#### **SURFACE PREPARATION:**

Surfaces must be dry and free from dust, dirt, grease, oil, or other foreign matter.

**APPLICATION:**

Apply by garden sprayer, airless, air assisted, or air spray equipment. Pour primer from container into sprayer and fine spray mist over entire substrate. Primer may also be applied by brush or roller. Allow primer to dry to a tacky film before applying membrane. Primer surfaces not covered by membrane during same work day must be reprimed. Do not dilute.

**CLEAN UP:**

For uncured film use water. Use mineral spirits for cured films.

**SAFETY**

Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and material safety data sheets before using. While all statements, technical information, and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user.

Please contact ErgonArmor for further information at 877.982.7667 or FAX 601-933-3381. For all Terms and Conditions of Sale see [ergonarmor.com](http://ergonarmor.com).

**ORDERING INFORMATION**

For additional information, prices, or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call 877-98ARMOR.

